

NVRHD-IP04P NVRHD-IP08P



Features

- H.264 / MPEG / JPEG Codec acceptable
- Manage Video & Audio & PTZ Control from IP cameras
- Max. 1080p 4ch, 8ch Decoding & Display
- Auto Searching & Setting IP camera in LAN
- Network access up to 25 users
- Supports Max. 2HDDs up to 6TB
- Support PoE (4ch: 4prots, 8ch: 8prots)
- User friendly Full-HD GUI

Specifications

| ITEM | | NVRHD-IP04P | NVRHD-IP08P |
|-------------------------|--|--|--|
| Video | IP Camera input | 4ch (4ch@1080p or 720p) | 8ch (8ch@1080p or 720p) |
| | Output | 1 HDMI , 1 VGA | |
| Audio | Input via network/ output | 4/1 | 8/1 |
| Sensor In / Alarm Out | | 4/1 | 4/1 |
| Operation System | | Embedded Linux OS | |
| Display | HDMI Resolution | 1920 x 1080P, 1920 x 1080i | |
| | VGA Resolution | 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080 | |
| | Split Display | 1/4 way | 1/4/9 way |
| Recording | Compression | H.264 / MPEG4 / JPEG | |
| | Resolution (Pixel) | 1080P(1920x1080) / 720P(1280x720) / D1(720x480/720x576) | |
| | Mode | Normal, Event(Alarm/Motion), Schedule | |
| | Rec Frame | 120fps@1080p 120fps@720p 120fps@D1 | 120fps@1080p 240fps@720p 240fps@D1 |
| Playback | Split Display | 1/4 way | 1/4/9 way |
| | Search Mode | Date & Time, Calendar, Event(Alarm/Motion), Bookmark | |
| | Mode | Normal, REW(*1,*2,*4,*8,*16) & FF(*1,*2,*4,*8,*16) Frame to Frame, Pause | |
| Network | Network Interface | Ethernet*2 (for IP Camera, Client PC) | |
| | Protocol | TCP/IP, SMTP, HTTP, DHCP, PPPOE(ADSL), RTP/RTSP | |
| | Serial Communication | RS-485 x2 (PTZ & Keyboard Control) | |
| | Web Browser | Internet Explorer 5.0 Higher (NVR Control or Monitoring) | |
| | Event Transport | E-mail notification when Event occurs | |
| | Viewing/ User Access | PC Client, CMS, Mobile Viewer / Up to 25 users | |
| Archive | Interface | USB 2.0 x2 | |
| | Archive Device | Network, USB Memory Stick | |
| Event | Motion Detection | Area : Programmable motion detection area for each camera Sensitivity : 10 Steps for each channel | |
| | Event Log | Up to 5000 events (Alarm, Motion, Video&Power Loss, Power&Record On/Off) | |
| Control | Controller | IR Remocon / Mouse | |
| | PTZ Camera | Control From RS485 Interface / Via Network | |
| Others | HDD / ODD | Support Max. 2 HDDs up to 6TB | |
| | Power Source | System | DC 12V/3.5A |
| | | PoE | DC 48V/1A |
| | Power Consumption | 40W | |
| Dimensions (Unit / Box) | 352(W)x252(D)x71(H)mm, 3kg / 400(W)x340(D)x145(H)mm, 4kg | | |

(*) Design and specifications are subject to change for product improvements without prior notice.